

Changes in Loading Standards Effective January 2012							
		Peak Periods		Off-Peak Periods			
				Headway above 10 minutes		Headway 10 minutes or better	
		Old	New	Old	New	Old	New
<b>Offpeak to Peak Ratios</b>							
<b>Buses</b>							
	Orion VII 12-metre low-floor bus (38 seats)			76%	69%	76%	87%
	Orion VII 12-metre low-floor bus (36 seats)			75%	68%	75%	85%
	New Flyer D40LF 12 metre low-floor bus			74%	67%	74%	85%
	High-floor lift-equipped 12-metre bus			71%	63%	71%	79%
<b>Streetcars</b>							
	Standard 15-metre streetcar (CLRV)			57%	57%	57%	72%
	Articulated 23-metre streetcar (ALRV)			56%	56%	56%	70%
<b>New Off Peak to Old Off Peak Ratios</b>							
<b>Buses</b>							
	Orion VII 12-metre low-floor bus (38 seats)			76%	76%	76%	96%
	Orion VII 12-metre low-floor bus (36 seats)			75%	75%	75%	94%
	New Flyer D40LF 12 metre low-floor bus			74%	74%	74%	94%
	High-floor lift-equipped 12-metre bus			71%	71%	71%	88%
<b>Streetcars</b>							
	Standard 15-metre streetcar (CLRV)			57%	57%	57%	72%
	Articulated 23-metre streetcar (ALRV)			56%	56%	56%	70%